




**BALL LIGHT
WALL MOUNTED, 2009**

Polished Brass, Polished Nickel-plated and Brass Black patinated Stainless Steel.




OVERALL DIMENSIONS






BACKPLATE DIMENSIONS

Mounting screws not included
5mm countersunk screw recommended



MATERIALS AND FINISHES

-  MA-BLWM-PBR
Polished Brass
-  MA-BLWM-PN
Polished Nickel
-  MA-BLWM-B
Black Patinated

BULB SPECIFICATIONS

E14 G9 Retrofit 33W 240V Halogen Bulb
ø45mm White Globe
458lm / 2700k

PRODUCT SPECIFICATIONS

Input voltage: 240V
Maximum wattage: 40W
240V Dimmable
Product weight: 1kg

CLEANING INSTRUCTIONS

Before cleaning, lighting fixtures must be turned off and unplugged from mains electricity. Whilst cleaning please take care and use the gloves provided.

Polished brass: As the item is unlacquered it will naturally oxidise and darken. Upon touching the items without gloves, fingerprints are likely to occur and leave marks. Use a good quality brass cleaning liquid and follow the product instructions using the extra soft dust cloth. Do not apply pressure on persistent marks. Remove them using repeated gentle motions and by reapplying the brass cleaning liquid.

Polished nickel: Use a lightly damp soft dust cloth and gently go over marks until clean. Dry it afterwards with a soft dust cloth.

Black patinated: Use a dry soft dust cloth and gently go over marks until clean. The brass patina is achieved through an artisanal technique of applying pigments by hand during a hot patination process. Through this alchemic process, the brass is transformed whilst retaining the material's inherent qualities. It will mature and change over time. The manner and speed in which it will change will depend on the environment, handling and the level and frequency of maintenance. Verdigris can also appear when the copper in the brass begins to oxidise.

Opaline Glass: Remove the opaline glass from the product. Using a lightly damp cloth, clean only the outside of the sphere. Only put the glass sphere back on the product once it is fully dry.